



Kolb Vertriebs GmbH

Neuer Weg 32
71111 Waldenbuch
Germany

Tel: +49 (0) 7157 27585

Fax: +49 (0) 7157 72901

info@u-kolb-gmbh.de

www.u-kolb-gmbh.de

Feeding Unit ZG 200

The compact feeding unit ZG 200 B2 has been developed as an active feeding system for the processing of cables, stranded wires, and tube materials. For example, with the ZG 200 B2 feeding unit, conductors from coils, Conipacks, from cable drums, cable shelves or tube coils can be pulled off optimally and fed into the downstream processing cycle. In this regard, preliminary transport occurs via two synchronously running, coated toothed belts. Fine, coarse or non-round cables can be fed forcefully and gently. Retooling is fast and easy.

The ZG 200 B2 is equipped with a mechanical upper belt delimitation that enables safe and gentle processing even of pressure-sensitive materials.

	ZG200-B2	ZG200-B2	ZG200-B2	ZG200-B2S
Power	370 Watt	550 Watt	750 Watt	560 Watt
Drive motor	Direct current	Direct current	Direct current	Servo
Throughput height	30,0 mm	30,0 mm	30,0 mm	30,0 mm
Throughput width	30,0 mm	30,0 mm	30,0 mm	30,0 mm
Speed	0,9 / 1,35 / 1,93 / 2,70 m/s	0,9 / 1,35 / 1,93 / 2,70 m/s	0,9 / 1,35 / 1,93 / 2,70 m/s	2,7 m/s
Length incl. arm	84 cm	84 cm	84 cm	84 cm
Width	48 cm	48 cm	48 cm	48 cm
Height	48 cm	48 cm	48 cm	48 cm
Coil weight maximum	40 kg	65 kg	100 kg	100 kg
Weight	53 kg	55 kg	57 kg	51 kg
Pneumatic supply	3 bar / 22 psi	3 bar / 22 psi	3 bar / 22 psi	3 bar / 22 psi
Electric supply	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Power supply optionally	110 V / 60 Hz	110 V / 60 Hz	110 V / 60 Hz	110 V / 60 Hz
Discharge height with optional base stand	109 cm	109 cm	109 cm	109 cm